




H 107

1" Dome H 107, High Fidelity Dome Tweeter

Chassis: aluminium, black.
Diaphragm: soft dome, polyamide, black.
Mounting holes: 4 x 5 mm, equispaced on PCD 95 mm.

The H 107 is a 1" dome tweeter featuring high efficiency and smooth response in its operating range. With proper filtering the H 107 can be used in two way systems with more than 50 W power handling capacity.

The soft diaphragm of the H 107 is vacuum formed from a high loss plastic foil with a shape optimized for the high frequency range.



Technical data:

8 ohms


Recommended frequency range	3000-25 000	Hz	Voice coil resistance:	4,8	ohms
Nominal power (DIN 45573)	50	W 1)	Effective diaphragm area	7	cm²
Music power (DIN 45500)	-	W	Moving mass	0,3	g
Characteristic sensitivity (1m,1w)	91	dB SPL	Free air resonance	1000	Hz
Operating power (DIN 45500):	3,2	W	Weight	0.56	kg
Voice coil diameter	26	mm	Magnet weight	0,25	kg
Voice coil height	1,5	mm			
Air gap height	2.0	mm			
Flux density:	1,8	T			
Force factor	3,5	Wb/m			

1) Crossover frequency 4000 Hz, 12 dB/oct.


NOTES:

Response curves recorded in anechoic chamber (Free-Field, 4π -radiation) with 0.5 m microphone distance. The loudspeaker is mounted in a 0.6 m by 0.8 m baffle:

A Sound pressure on and off axis, and impedance:




B Sound pressure and distortion on axis. The distortion components are raised by 20 dB:



C Sound pressure response to 4 Volts step function:

Sound
pressure
0.56 Pa/div



0.2ms/div Time →



Seas Fabrikker a.s
P.O.Box 600, Høyden, N-1501 Moss, Norway
Phone +47-32-65 811
Telex N 18419

Note: New telex no. 78419 SEAS N from June 20. 1985